



WL350 Firewall™

Drinking water you can trust for your office.

The Waterlogic WL350 brings breakthrough Firewall water purification to your office in a compact model design. With high performance filtration and Firewall ultraviolet technology that purifies water to 99.9999% bacteria free, you can now provide the best in water quality to your employees.



Your Total Water Solution

The WL350 has three core technologies:



High Performance Filtration

Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



Firewall™ Advanced UV Purification

Firewall ultraviolet light purifies the water to 99.9999% bacteria free. It acts as a final barrier to pathogens right at the point of dispensing.



BioCote® Anti-Microbial Protection

Plastic surfaces surrounding the dispensing area are infused with BioCote.®

*For more information visit www.biocote.com/home-us.

Good for the Earth

Waterlogic coolers have been shown to reduce carbon footprint by up to 55% compared to bottled water coolers. *

Bottleless water coolers reduce plastic bottle contribution to landfills.

The WL350 is ENERGY STAR certified

*PHS Waterlogic 2012. www.phswaterlogic.com/carbonreductionlabel.aspx



Our Firewall™ technology is unique for 3 reasons:

1. Intense UV purity

The design allows for higher UV exposure which reduces bacteria, viruses and parasites that may be in the water, purifying the water up to 99.9999% of any bacteria 100% of the time.

2. Goodbye bacterial contamination

Point of dispense purification keeps the dispense nozzle free from external contamination as well as purifying the water as it fills your cup, making the freshest water possible.

3. Certified, twice

The Firewall™ technology has been tested and certified by the Water Quality Association to NSF/ANSI-55 Class A UV and NSF/P231 US EPA standard for microbiological water



WL350 Countertop Model

Tested and Certified

Firewall UV technology is certified by the WQA






Waterlogic Filters are certified by the WQA






Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

See business card for local distributor or visit www.waterlogic.us



Water Options	Technical Features	
 Cold water	Countertop dimensions	13.75" (W) x 17.75" (H) x 14.5" (D)
 Hot water	Tower dimensions	13.75" (W) x 41" (H) x 14.5" (D)
	Dispense area height	8.5"
	Weight	Countertop: 58 lbs Tower: 66 lbs
	Filtration included	Carbon Block (CBC) 1 micron with lead and cyst reduction
	Additional features	Firewall™ UV sensor Thermal overload safety protection Energy saving sleep mode (programmable) Child safeguard dispensing system Built in leak detection
	Capacity	Hot tank: 1.6 liters Cold tank tower: 4 liters Cold tank countertop: 2 liters
	Compressor	110v / 60Hz LG compressor

02-041402